

CPRA 1000-T/1200-T

Fully thyristorised heavy duty SAW & gouging

SAW process produces the highest quality welds at speeds higher than MMA or MIG process. Standard single wire SAW can deposit up to 5 kg/hr and automatic multi-wire technique can reach much higher levels

CPRA 1000-T/1200 – **T** are reliable power sources offered with AWM (LW) tractor for single wire SAW applications.

Salient Features

CPRA 1000-T / 1200-T

Rugged construction.

Rubberized wheels for ease of mobility.


For applications up to 1000A/1200A max

Precise voltage control.

Mains voltage compensation.

Protection against thermal overloading

LW control panel



AUTO WELD MAJOR (LW) THY

Reliable wire feeding.

4 wheel tractor mounted with 2m track.

Up to 1200A max applications.

Mechanical pointer for tracking.

Wire inch up / down.

INPUT







OUTPUT

PROCESS













POWER SOURCE	CPRA 1000-T	CPRA 1200-T
Mains supply, Ph x V, Hz	3 x 415, 50	3 x 415, 50
Fuse rating at 415V, A (Max)	100	125
Input power kVA (Max)	66	82
Open circuit voltage, V DC	59	59
Welding current range	300 A /32 V -1000 A/44 V	300 A /32V -1200 A /44 V
Welding current at 60% duty cycle, A	1000	1200
Welding current at 100% duty cycle, A	850	950
Insulation class	F	F
Type of cooling	Forced Air	Forced Air
Dimensions, I x w x h, mm	830 x 670 x 1400	830 x 670 x 1400
Weight, Kg	440	440

WELDING HEAD	AUTO WELD MAJOR (LW) THY
Wire (single) diameter range, mm	2.4 – 5.0 (Standard), 6.3 (Optional)
Wire feed speed, cm/min	50 – 450
Welding current, A	1200 max (800A continuous)
Vertical adjustment, mm	140
Horizontal adjustment, mm	140
Swivel arrangement, Deg	360°
Torch tilt, Deg	\pm 45 $^{\circ}$
Speed range of tractor, cm/min	0 – 150
Hopper capacity, Kg	5
Wheel center of tractor, cm	350
Dimension, I x w x h, mm	1368 x 410 x 1145

ORDERING INFORMATION

CPRA 1000-T 4620649500 **CPRA 1200-T** 4620649600 Auto Weld Major (LW) THY 4620652737 Track for Auto Weld Major (LW) 4621649351

SAW TRACTOR LW is supplied with 2m track, 1 set of control cable, 1 pair of Cu 70 sq mm welding cable (each 15m in length) and 1 pair of 5m long Cu 70 sq mm welding cable with Earth Clamp.

ESAB helps you get the best butt or fillet welds





Quality accessories for the quality welder

ESAB offers a wide range of accessories. The complete range, along with product information, is available at our local web-sites, look at www.esab.com or contact your local ESAB dealer.







ESAB is certified according to ISO 9001



The ESAB group is certified according to ISO 14001 & **OHSAS 18001**



Registered and Head Office: 13, Industrial Estate, III Main Road, Ambattur, Chennai - 600058. Tel : 044-42281100 Fax : 044-42281150 Equipment Factories: Taratala, Kolkata and Irungattukottai, Chennai



nal Sales: Email: equipment.sales@esab.co.in

hi 110015 : (011) 4142 7091 : (011) 4142 7099

tu Centre, 6th Floor 634, Anna Salai am, Chennai 600035

Central Regional Office
No. 218, Ashirvad
South Ambazari Road
Bajaj Nagar, Nagpur 440010 (0712) 222 9547 / 48 (0712) 222 9549